FUJIFILM X-A3 Specifications

Model Name		FUJIFILM X-A3
Number of effective pixels		24.2 million pixels
Image sensor		23.5mmx15.7mm(APS-C) CMOS with primary color filter
Sensor Cleaning system		Ultra Sonic Vibration
Storage media		SD Card (-2G) / SDHC Card (-32G) / SDXC Card (-256G) UHS-I *1
File format	still image	JPEG (Exif Ver 2.3 *2) RAW (RAF format)/RAW+JPEG(Design rule for Camera File system compliant, DPOF-compatible)
	movie	Movie File Format : MOV Movie Video Compression : H.264 Audio : Linear PCM Stereo
Number of recorded pixels		L: (3:2) 6000 x 4000 / (16:9) 6000 x 3376 / (1:1) 4000 x 4000 M: (3:2) 4240 x 2832 / (16:9) 4240 x 2384 / (1:1) 2832 x 2832 S: (3:2) 3008 x 2000 / (16:9) 3008 x 1688 / (1:1) 2000 x 2000 <Motion Panorama> 180°: Vertical: 2160 x 9600 / Horizontal: 9600 x 1440 120°: Vertical: 2160 x 6400 / Horizontal: 6400 x 1440
Lens mount		FUJIFILM X mount
Sensitivity		Standard Output Sensitivity : AUTO1 / AUTO2 / AUTO3(up to ISO6400) / ISO200 to 6400(1/3 step) Extended output sensitivity : ISO100 / 12800 / 25600
Exposure control		TTL 256-zones metering, Multi / Spot / Average
Exposure mode		P(Program AE) / A(Aperture Priority AE) / S(Shutter Speed Priority AE) / M(Manual Exposure)
Exposure compensation		-3.0EV - +3.0EV, 1/3EV step (movie recording : -2.0EV - +2.0EV)
Image Stabilizer		Supported with OIS type lens
Face Detection		Yes
Eye Detection		Yes
Shutter type		Focal Plane Shutter
Shutter speed	Mechanical Shutter	4 sec. to 1/4000 sec.(P mode), 30 sec. to 1/4000 sec.(All modes) Bulb mode(up to 60 min), TIME : 30 sec. to 1/4000 sec.
	Electronic Shutter *3	1 sec. to 1/32000 sec.(P / A / S / M modes) Bulb mode : 1 sec. fixed, TIME : 1 sec. to 1/32000sec.
	Mechanical + Electronic Shutter	4 sec. to 1/32000 sec.(P mode), 30 sec. to 1/32000 sec.(All modes) Bulb mode(up to 60 min), TIME : 30 sec. to 1/32000 sec.
	Synchronized shutter speed for flash	1/180 sec. or slower
Continuous shooting		Approx. 6.0 fps (JPEG : max. approx. 10 frames) Approx. 3.0 fps (JPEG : max. approx. 50 frames) *Recordable frame number may vary depending on the type of memory card used. *The frame rate varies with shooting condition and the number of images recorded.
Auto bracketing		AE Bracketing (±1/3EV, ±2/3EV, ±1EV) Film Simulation Bracketing (Any 3 types of film simulation selectable) Dynamic Range Bracketing (100%, 200%, 400%) ISO sensitivity Bracketing (±1/3EV, ±2/3EV, ±1EV) White Balance Bracketing (±1, ±2, ±3)
Focus	mode	Single AF / Continuous AF / MF / AF+MF
	type	TTL contrast AF, AF assist illuminator available
	AF frame selection	Single point AF: 7x7 (Changeable size of AF frame among 5 types), Zone AF: 3x3 / 5x3 / 5x5 from 77 areas on 11x7 grid, Wide/Tracking AF: (up to 9 area) *AF-S : Wide *AF-C : Tracking
White balance		Automatic Scene recognition / Custom1–3 / Color temperature selection (2500K–10000K) / Preset: Fine,Shade, Fluorescent light (Daylight), Fluorescent light (Warm White), Fluorescent light (Cool White),Incandescent light, Underwater
Self-timer		2sec. / 10sec. / Smile / Buddy (LV.1 - LV.3) / Group (1-4 subjects)
Flash		Manual pop-up flash (Super Intelligent Flash) Guide number : Approx 5 (ISO100.m) / Approx 7 (ISO200.m)
Flash modes		Red-eye removal OFF: Auto/Forced Flash/Suppressed Flash/Slow Synchro/Rear-curtain Synchro/Commander Red-eye removal ON: Red-eye Reduction Auto/Red-eye Reduction & Forced Flash/Suppressed Flash/ Red-eye Reduction & Slow Synchro/Red-eye Reduction & Rear-curtain Synchro/Commander *Red-eye removal is active when Face Detection is set to ON.

Hot shoe		Yes (dedicated TTL Flash compatible)
LCD monitor		3.0-inch, aspect ratio 3:2, approx. 1,040K-dot Tilt-type, TFT color LCD monitor (approx. 100% coverage)
Movie recording		Full HD 1920 x 1080 60p / 50p / 24p, Continuous recording : up to approx. 14 min. HD 1280 x 720 60p / 50p / 24p, Continuous recording : up to approx. 27 min. *Use a card with SD Speed Class with CLASS10 or higher
Mode dial		Advanced SR AUTO / P / S / A / M / C(Custom) / Night / Sports / Landscape / Portrait Enhancer / SP(Scene Position) / Adv.
Film Simulation mode		11 type (PROVIA/STANDARD, Velvia/VIVID, ASTIA/SOFT, CLASSIC CHROME, PRO Neg Hi, PRO Neg. Std, MONOCHROME, MONOCHROME+Ye FILTER, MONOCHROME+R FILTER, MONOCHROME+G FILTER, SEPIA)
Dynamic range setting		AUTO, 100%, 200%, 400% ISO restriction (DR100%: No limit, DR200%: ISO400 or more, DR400%: ISO800 or more)
Advanced filter		Toy camera, Miniature, Pop color, High-key, Low-key, Dynamic tone, Fish-eye, Soft focus, Cross screen, Partial color (Red / Orange / Yellow / Green / Blue / Purple)
Touch screen		Shooting Mode : Shooting, AF, Focus area, Digital zoom, Protrait enhancement level (Portrait Enhancer mode) Display Mode : Swipe, Zoom, Pinch-in / Pinch-Out, Double-tap, Drag
Other photography functions		Advanced SR AUTO, Eye detection AF, Face Detection, Interval timer shooting, Auto Red-eye Removal, Select custom setting, Motion panorama, Color space, Setting (Color, Sharpness, D-range, Gradation), Film Simulation, Advanced Filter, Framing guideline, Frame No. memory, Histogram display, Preview depth of focus, Pre-AF, Focus check, Focus Peak Highlight, Multiple exposure, Release priority / Focus priority selection, Fn button setting, ISO AUTO control, Interlock spot AE & Focus area, Edit/Save quick menu, Preview exp./WB in manual mode, Shutter Type, Touch screen setting
Playback functions		RAW conversion, Image rotate, Auto image rotate, Face Detection, Red-eye reduction, Photobook assist, Erase selected frames, Multi-frame playback (with micro thumbnail), Slide show, Protect, Crop, Resize, Panorama, Favorites
Wireless transmitter	standard	IEEE 802.11b/g/n (standard wireless protocol)
	access mode	Infrastructure
Wireless function		Geotagging setup, Image transfer (Individual image/Selected multiple images), View & Obtain Images, PC Autosave, instax Printer Print
Other functions		PictBridge, Exif Print, 35 Languages, Date/Time, Time difference, Sound & Flash OFF, Quick start Mode, High Performance, Preview exp. in Manual mode, LCD Brightness, LCD Color, Preview Pic. Effect, DISP. Custom Setting
Terminal	Video output	–
	Digital interface	USB 2.0 High-Speed / micro USB terminal *connectable with Remote Release RR-90 (sold separately)
	HD output	HDMI Micro connector (Type D)
Power supply		NP-W126S Li-ion battery (included)
Dimensions		116.9(W) mm x 66.9 (H) mm x 40.4(D) mm / 4.6 in.(W) x 2.6 in. (H) x 1.6 in. (D) (Minimum depth: 31.6 mm/ 1.2 in.)
Weight		Approx. 339g / 12.0 oz. (including battery and memory card) Approx. 290g / 10.2 oz. (excluding accessories, battery and memory card)
Operating	Temperature	0 - 40°C / 32-104°F
	Humidity	10 - 80% (no condensation)
Battery life for still images *4		approx 410 frames (with XF35mmF1.4 R lens)
Starting up period		Approx. 0.7 sec., when High Performance mode set to ON Approx. 1.3 sec., when High Performance mode set to OFF *Fujifilm research
Accessories included		Li-ion battery NP-W126S, AC power adapter AC-5VF, Plug Adapter, USB cable, Shoulder strap, Body cap, Owner's manual

*1 Please see the Fujifilm website (http://www.fujifilm.com/support/digital_cameras/compatibility/card/x/) to check memory card compatibility.
*2 Exif 2.3 is a digital camera file format that contains a variety of shooting information for optimal printing.
*3 The Electronic Shutter may not be suitable for fast-moving objects. Flash can not be used.
*4 Approximate number of frames that can be taken with a fully-charged battery based on CIPA standard.

For more information, please visit our website:

http://fujifilm-x.com/x-a3/

To ensure correct usage, read owner's manual carefully before using your equipment.
All photos, illustrations, drawings and other images in this brochure are intended for illustrative purposes only.

DXC logo is a trademark. All other trademarks are the property of their respective holders.
SILKYPIX® is a registered trademark of Ichikawa Soft Laboratory Co., Ltd. in Japan.

PictBridge Exif Print DPOF SDXC I HDMI

Specifications are subject to change without notice
For more information, please visit our website
http://www.fujifilm.com/products/digital_cameras/index.html

FUJIFILM
FUJIFILM Corporation

©2016 FUJIFILM Corporation

FUJIFILM
Value from Innovation

X-A3

My most valuable possessions are always with me

Wherever I go my world is filled with vibrant colors

Selfie

The 180-degree tiltable LCD monitor allows you to check your composition and facial expression before taking a picture.
In the Selfie mode, the command dial on the rear panel lets you operate the AF and shutter for simple shooting.

Eye Detection AF

The Eye detection AF function is automatically activated when you rotate the tilting LCD panel. It helps to achieve superior selfies by focusing on the eyes.



Portrait Enhancer Mode

The camera makes automatic adjustments to enhance skin tones for better portrait shots.
The Portrait Enhancer mode can be applied on three levels.

Enhancer Level 1

Enhancer Level 3

Wireless Communication

The camera has a built-in Wi-Fi capability to connect to Instax SHARE for on-the-spot printing, transfer photos to your smartphone or tablet, or even enable remote-shooting.

Touchscreen

The LCD monitor features a touchscreen panel for intuitive control, just like a smartphone.

Super Intelligent Flash

The camera automatically adjusts flash output to suit every scene, producing a natural photo with reduced highlight or shadow clipping.

Top: Shot with a regular flash
Bottom: Shot with the Super Intelligent Flash

Macro

Get up close and personal to your subject, up to 7cm (from the front edge of the lens) for better macro photography.

ASTIA / Soft

Velvia / VIVID

Film Simulation Mode

Create that perfect analog look and feel
using one of our 11 unique film simulation modes.

Advanced Filters

Ten advanced filters enhance your artistic freedom further. No need for hours of editing, much easier than shooting with your smartphone

Toy camera

Miniature

Soft focus

Patial color (Red)

24M APS-C Sensor

The camera features a large, 24.2 megapixel APS-C sensor, the same size used in most DSLRs. For stunning high quality images, smooth bokeh and even the atmosphere of the scene, far superior to any smartphone.

Self Timer

The Self Timer now features Smile Detection, Buddy Timer and Group Timer modes, capturing that special moment your friends have the perfect facial expression.

USB Charging

The camera can be charged through USB connection just like your phone.

Standard Lens

XC16-50mm F3.5-5.6 OIS II

The standard zoom lens supplied with the X-A3 covers the focal lengths equivalent to 24-76mm*. The compact lens weighs just 195g, and features image stabilization equivalent to 3 stops and a close working distance of just 7cm from the lens surface.

*35mm format equivalent

Accessories

Li-ion Battery
NP-W126S

Battery charger
BC-W126

AC Power Adapter
AC-9V

DC Coupler
CP-W126

Macro Extension Tube
MCEX-11
MCEX-16

M Mount Adapter
MM ADAPTER

Remote Release
RR-90

Shoe Mount Flash
EF-X500
EF-42
EF-20
EF-X20

Grip Belt
GB-001

All XF / XC lenses, which boast high descriptive performance, can be used with the X-A3.
>> http://fujifilm-x.com/lenses/